

**WEARMASTER  
MASONRY SURFACE SEALER  
\*PERFORMANCE LINE\***

**DESCRIPTION**

---

Scot's TUFF™ *Wearmaster* Masonry Surface Sealer *\*Performance Line\** is a water-based acrylic sealer specifically formulated to protect concrete, quarry tile, grout, marble, terrazzo and masonry surfaces. *Wearmaster* is easy and economical to apply, produces no solvent odor, and dries to a durable wear-resistant finish. This sealer protects hard surfaces from soil, rubber marks, oil, grease and most solvents, while preventing dusting of concrete.

**APPLICATION AND USES**

---

Use *Wearmaster* on all concrete, stone, and masonry surfaces where a durable wear-resistant finish is required. *Wearmaster* has excellent adhesion without acid etching, no solvent odor, and is fast drying. This penetrating sealer will prevent the "dusting" of concrete and stone surfaces.

**DIRECTIONS FOR USE**

---

Floor Preparation: Do not apply on concrete less than 30 days old. Clean and rinse floor thoroughly. Floor must be clean of soil, dirt, oil, and grease to insure a strong bond with *Wearmaster Masonry Surface Sealer*. Acid etching is not required for bonding. Floor must be clean and thoroughly dry.  
Application: For best results, apply with a string mop or airless sprayer. Allow 45 minutes to 2 hours drying time between coats. NOTE: Never pour unused portion into original container; it will contaminate unused product.

**FEATURES AND BENEFITS**

- No offensive solvent odor
- Excellent adhesion without etching
- Fast drying and self leveling
- Penetrating seal

**TECHNICAL DATA**

Appearance..... Milky liquid  
pH..... 9  
Slip Resistance.. > 0.5 (James Machine)  
Stability..... Heat stable, keep from freezing

| <b>ITEM #</b> | <b>PACKAGED</b> | <b>DILUTION RATIO</b> | <b>COVERAGE RATE</b>       |
|---------------|-----------------|-----------------------|----------------------------|
| 0A4711        | 1 Gallon Round  | 4/case                | 1500 - 2000 sq. ft./gallon |
| 0A4712        | 5 Gallon Pail   | each                  | (depending on porosity     |
| 0A4713        | 55 Gallon Drum  | each                  | of floor)                  |